

**LANDA**<sup>®</sup>  
CLEANING SYSTEMS

Since 1969

Industrial Pressure Washers and Parts Washers  
...Built Right to Do the Job Right

# HOT

Portable, Electric-Powered,  
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Landa Belt-Drive Pump with 7-Year Warranty
- Sch. 80 Heating Coil
- 120V, 208V, 230V
- True Steam Model



▲ Heavy-duty **Motor** and cast-iron, bushing **Pulleys** use a convenient 2-bolt pulley adjustment for easy maintenance and longer life; a "V" cogged belt connects the motor to the **Landa High-Pressure Pump**, which features three ceramic plungers and a forged brass head with five-year warranty.



■ High-efficiency **Burner** is protected by a cover and mounted on the end for easy access.

■ Conveniently located **Control Panel** with 3-position switch is housed in a water-resistant electrical box; anti-syphon detergent valve is optional.

■ 36 ft. of high-grade **Electrical Cord** with Ground Fault Circuit Interrupter on all models for operator safety.

■ 50 ft. of steel-wire braid **High Pressure Hose** with 24-inch guard for burst protection.


■ Unique, slide-out **Service Platform** allows for easy access and servicing of pump and unloader.

■ High-heat aluminized steel inner wrap surrounds cold-rolled **Heating Coil** made of Schedule 80 steel pipe with five-year warranty.

■ Unique design allows access to the **Coil Wrap** within minutes by simply removing six bolts.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ Quick-couple **Nozzle** is made of hardened stainless steel and mounted for ready access.



▲ Optional, E-Zee **Hose Reel** with compact, easy-wind design for tangle-free handling of hose.



■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain; safety brake prevents rolling.

■ Many **Safety Features**, including a rupture disk and thermal pump protector to prevent the build up of excessive pressures or heat.

■ Insulated, fatigue-free **Trigger Gun** with chrome-plated, dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.

■ Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection.

■ Easy-to-attach **Detergent Injector** for soap application.

[www.landa.com](http://www.landa.com)

# HOT

Portable, Electric-Powered,  
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Landa Belt-Drive Pump with 7-Year Warranty
- Sch. 80 Heating Coil
- 120V, 208V, 230V
- True Steam Model



## WHY CHOOSE LANDA'S HOT

The HOT is the most economical choice of Landa's electric-powered, diesel-heated hot water pressure washers featuring the heat-efficient horizontal coil. It is also the only line among those with a horizontal coil design that has a true steam cleaner, or steamer—the HOT 3-30034D.

**QUALITY:** The HOT boasts many of the same quality components of other Landa hot water pressure washers, including a belt-drive, tri-plunger high-pressure Landa pump with 7-year warranty, Schedule 80 heating coil made of 1/2-inch pipe and a slide-out service platform—a service tech's dream.

**PORTABILITY:** All of the HOT models weigh less than 500 lbs. and are evenly balanced on four leak-free, tubed, pneumatic tires for easy maneuvering in any terrain. Waffle grips on the two steering bars add to the HOT's portability.

**SAFETY:** Certified to the rigid UL-1776 safety standards, the HOT also has many features that make it extremely safe, including motor thermal overload protection, rupture disk attached to the heating coil, thermal pump protector, flow-activated fuel shut-off switch, 24-inch hose guard for burst protection, and Ground Fault Circuit Interrupter on all models.

## HOT Specifications

Part No.	GPM	PSI	Motor HP	Electrical	Amps	Pump	RPM	Temperature	L x W x H	SHIP WT.
HOT2-11024D	2.0	1000	1.5	120V	18	Landa	1100	Up to 200°F	48" x 29" x 36.5"	485 lbs.
HOT2-15024D	1.9	1500	2	120V	20	Landa	1100	Up to 200°F	48" x 29" x 36.5"	495 lbs.
HOT3-11024D	2.8	1000	2	120V	20	Landa	1375	Up to 200°F	48" x 29" x 36.5"	505 lbs.
HOT4-20024A	3.5	2000	5	230V 1 ph	25	Landa	1350	Up to 200°F	48" x 29" x 36.5"	530 lbs.
HOT4-20024G	3.5	2000	5	208V 1 ph	27	Landa	1350	Up to 200°F	48" x 29" x 36.5"	530 lbs.
HOT3-30034D Steamer	2.5	300	1.5	120V	12	Landa	1375	310°F	48" x 29" x 36.5"	445 lbs.

Note: We are constantly improving and updating our products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.

## OPTIONS: (SEE YOUR LANDA DEALER FOR A COMPLETE LIST OF OPTIONS)

Part No.	Description
30-410	Tire upgrade to Mag Wheels (Set of 4)
30-510	Float Tank and Inlet Detergent Metering Valve (All but 4-2000)
30-511	Float Tank and Inlet Detergent Metering Valve (4-2000 only)
30-512	Stainless Steel Outer Coil Wrap
4-02755030	E-Zee Hose Reel
30-5022	E-Zee Reel Mounting Kit
See Dealer	Automatic Start / Stop or Time Delay Shutdown are available upon request